

# NEO-7 series

## Versatile u-blox 7 GPS/GNSS modules

### Highlights

- Multi-GNSS engine for GPS, GLONASS, Galileo and QZSS
- Cost and performance optimized versions
- Combines low power consumption and high sensitivity
- Simple integration with u-blox wireless modules
- Backward compatible with NEO-6 and NEO-5 families



NEO-7 series:  
12.2 x 16.0 x 2.4 mm

### Product description

The NEO-7 series is the newest family of standalone GPS/GNSS modules from u-blox. With the exceptional performance of the u-blox 7 multi-GNSS (GPS, GLONASS, Galileo, QZSS and SBAS) engine, the NEO-7 series delivers high sensitivity and minimal acquisition times in the industry proven NEO form factor.

The NEO-7 series provides maximum sensitivity while maintaining low system power. The NEO-7M is optimized for cost sensitive applications, while NEO-7N provides best performance and easier RF integration. The industry proven NEO form factor allows easy migration from previous NEO generations. Sophisticated RF-architecture and interference suppression ensure maximum performance even in GPS-hostile environments.

The NEO-7 combines a high level of robustness and integration capability with flexible connectivity options. Future-proof the NEO-7N's internal Flash allows simple firmware upgrades for supporting additional GNSS systems. This makes NEO-7 perfectly suited to industrial and automotive applications. The DDC (I<sup>2</sup>C compliant) interface provides connectivity and enables synergies with u-blox SARA, LEON and LISA wireless modules. For RF optimization the NEO-7N features an additional front-end LNA for easier antenna integration and a front-end SAW filter for increased jamming immunity.

u-blox 7 modules use GPS/GNSS chips qualified according to AEC-Q100 and are manufactured in ISO/TS 16949 certified sites. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

### Product selector

Model	Type			Supply			Interfaces				Features													
	GPS	QZSS	GLONASS	Timing	Dead Reckoning	Precise Point Positioning	2.7 V – 3.6 V	1.65 V – 3.6 V	Lowest power (DC/DC)	UART	USB	SPI	DDC (I <sup>2</sup> C compliant)	Programmable (Flash)	Data logger	Extra front-end LNA	Front-end SAW filter	Oscillator	RTC crystal	Antenna supply	Antenna short circuit detection / protection	Antenna open circuit detection pin	Timepulse	External interrupt / Wakeup
NEO-7N	•	•	•				•	•		•	•	Sel	•	•	•	•		T	•	○	○	○	•	•
NEO-7M	•	•	•					•		•	•	Sel	•					C	•	○	○	○	•	•

Sel = Select for either SPI or UART/DDC by HW configuration pin (D\_SEL)  
○ = Optional, not activated per default or requires external components

C = Crystal / T = TCXO

## Features

Receiver type	56-channel u-blox7 engine GPS L1 C/A, GLONASS L1 FDMA, QZSS L1 C/A, Galileo E1B/C, Compass ready SBAS: WAAS, EGNOS, MSAS	
Navigation update rate	up to 10 Hz	
Accuracy	GPS	GLONASS
	Position	2.5 m CEP 4 m
	SBAS	2.0 m CEP n.a.
Acquisition	Cold starts:	29 s 30 s
	Aided starts:	5 s n.a.
	Reacquisition:	1 s 3 s
Sensitivity	Tracking:	-162 dBm -158 dBm
	Cold starts:	-148 dBm -140 dBm
	Warm starts:	-148 dBm -145 dBm
Assistance	AssistNow Online AssistNow Offline AssistNow Autonomous OMA SUPL & 3GPP compliant	
Oscillator	TCXO (NEO-7N), crystal (NEO-7M)	
RTC crystal	Built-In	
Anti jamming	Active CW detection and removal	
Memory	ROM (NEO-7M) or Flash (NEO-7N)	
Supported antennas	Active and passive	

## Electrical data

Supply voltage	1.65 V to 3.6 V (NEO-7M) 2.7 V to 3.6 V (NEO-7N)
Power Consumption	47 mW @ 1.8 V (Continuous) <sup>1</sup> 51 mW @ 3 V (Continuous) <sup>1</sup> 14 mW @ 1.8V Power Save mode (1 Hz) <sup>1</sup>
Backup Supply	1.4 to 3.6V

<sup>1</sup> NEO-7M.

## Interfaces

Serial interfaces	1 UART 1 USBV2.0 full speed 12 Mbit/s 1 SPI (optional) 1 DDC (I <sup>2</sup> C compliant)
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Timepulse	Configurable 0.25 Hz to 1 kHz
Protocols	NMEA, UBX binary, RTCM

### Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.


The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit [www.u-blox.com](http://www.u-blox.com).

Copyright © 2012, u-blox AG

## Package

24 pin LCC (Leadless Chip Carrier): 12.2 x 16.0 x 2.4, 1.6 g

Pinout



## Environmental data, quality & reliability

Operating temp.	-40° C to 85° C
Storage temp.	-40° C to 85° C
RoHS compliant (lead-free)	
Qualification according to ISO 16750	
Manufactured in ISO/TS 16949 certified production sites	
Uses u-blox 7 chips qualified according to AEC-Q100	

## Ordering information

NEO-7M-0	u-blox 7 GPS/GNSS Module, 1.65–3.6V, 12x16mm, 250 pcs/reel
NEO-7N-0	u-blox 7 GPS/GNSS Module, Flash, TCXO, SAW, LNA, 12x16mm, 250 pcs/reel

Available as samples and tape on reel

## Contact us

HQ Switzerland +41 44 722 7444 info@u-blox.com	China +86 10 68 133 545 info_cn@u-blox.com
--	--

EMEA +41 44 722 7444 info@u-blox.com	Japan +81 3 5775 3850 info_jp@u-blox.com
--	--

Americas +1 703 483 3180 info_us@u-blox.com	Korea +82 2 542 0861 info_kr@u-blox.com
---	---

APAC – Singapore +65 6734 3811 info_ap@u-blox.com	Taiwan +886 2 2657 1090 info_tw@u-blox.com
---	--