

NEO-7P

u-blox 7 precise point positioning GNSS module

Highlights

- High precision GNSS < 1 m
- DGPS by SBAS or RTCM
- Combines low power consumption and high sensitivity
- Simple integration with u-blox wireless modules
- Backward compatible with NEO-6 and NEO-5 families
- Raw measurement data (GPS)



NEO-7P:
12.2 x 16.0 x 2.4 mm

Product description

The NEO-7P module combines the high performance of the u-blox 7 multi-GNSS engine with precise point positioning (PPP) technology for GPS. u-blox' industry-proven PPP algorithm, in combination with SBAS, provides exceptional precision in clear-sky applications without the need for a reference station. This makes NEO-7P the ideal solution for many applications in surveying, marine navigation, agriculture, sports and leisure.

For world-wide application, the NEO-7P supports Differential GPS (DGPS) operation as an alternative to SBAS and PPP, using RTCM correction messages from a local reference station or aiding network. Ionospheric corrections received from regional SBAS satellites (WAAS, EGNOS, MSAS) enable the highest stand-alone positioning accuracy from the PPP algorithm. u-blox' PPP also provides useful improvements in stand-alone precision even without SBAS. PPP delivers its full benefits after the first few minutes of operation with an unobstructed sky view.

The entire NEO-7 series combines excellent sensitivity with low power and includes variants optimised for cost and performance. The industry-proven NEO form factor allows easy migration from previous NEO generations. The NEO-7P features a front-end SAW RF filter for increased jamming immunity. This is reinforced by sophisticated RF-architecture and interference suppression, ensuring maximum performance even in hostile signal environments. UART, USB and DDC (I2C compliant) interfaces provide flexible connectivity and synergies with u-blox SARA, LEON and LISA cellular wireless modules. The NEO-7P's internal Flash allows simple firmware upgrades.

u-blox 7 modules use GNSS chips qualified according to AEC-Q100 and are manufactured in ISO/TS 16949 certified sites. Qualification tests are performed as stipulated in the ISO16750 standard: " Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

Product selector


Model	Type	Supply	Interfaces	Features
	GPS / QZSS GLONASS BeiDou Galileo Timing & Frequency Dead Reckoning Precise Point Positioning	1.65 V – 3.6 V 2.7 V – 3.6 V Lowest power (DC/DC)	UART USB SPI DDC (I2C compliant)	Programmable (Flash) Data logging Extra front-end LNA Front-end SAW filter RTC crystal Internal oscillator Antenna supply Antenna short circuit detection / protection Antenna open circuit detection pin Timepulse output External interrupt / Wakeup
NEO-7P	• •	• •	• • Sel •	• • • C • • • • •

QZSS only with Standard Point Positioning
C = Crystal / T = TCXO


○ = Optional, not activated per default or requires external components
Sel = Select for either SPI or UART/DDC by HW configuration pin (D_SEL)

Features

Receiver type	56-channel u-blox 7 engine GPS L1 C/A, GLONASS L1 FDMA, QZSS L1 C/A, SBAS: WAAS, EGNOS, MSAS		
Navigation update rate	Up to 10 Hz		
Accuracy	GPS	GLONASS	
	Position:	2.5 m CEP	4 m
	SBAS:	2.0 m CEP	n.a.
Acquisition	SBAS + PPP:	< 1 m CEP	n.a.
	Cold starts:	29 s	30 s
	Aided starts:	5 s	n.a.
Sensitivity	Reacquisition:	1 s	3 s
	Tracking:	-162 dBm	-158 dBm
	Cold starts:	-148 dBm	-140 dBm
Assistance	Warm starts:	-148 dBm	-145 dBm
	AssistNow Online		
	AssistNow Offline		
Oscillator	AssistNow Autonomous		
	OMA SUPL & 3GPP compliant		
	Crystal		
RTC crystal	Built-In		
Anti jamming	Active CW detection and removal		
Memory	Flash		
Supported antennas	Active		



Accuracy with PPP+SBAS
(units in m)



Accuracy with GPS and SBAS
(units in m)

Interfaces

Serial interfaces	1 UART 1 USBV2.0 full speed 12 Mbit/s 1 SPI (optional) 1 DDC (I ² C compliant)
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Timepulse	Configurable 0.25 Hz to 1 kHz
Protocols	NMEA, UBX binary, RTCM

Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.


The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.

Copyright © 2013, u-blox AG

Package

24 pin LCC (Leadless Chip Carrier): 12.2 x 16.0 x 2.4 mm, 1.6 g

Pinout



Environmental data, quality & reliability

Operating temp. -40° C to 85° C

Storage temp. -40° C to 85° C

RoHS compliant (lead-free)

Qualification according to ISO 16750

Manufactured in ISO/TS 16949 certified production sites

Uses u-blox 7 chips qualified according to AEC-Q100

Electrical data

Supply voltage 2.7 V to 3.6 V

Power Consumption 70 mW @ 3 V (Continuous)

Backup Supply 1.4 to 3.6V

Ordering information

NEO-7P-0 u-blox 7 LCC Module, GNSS
Precise Point Positioning, Raw Data
12.2x16 mm, 250 pcs/reel, 3 V

Available as samples and tape on reel

Contact us

HQ Switzerland / EMEA
+41 44 722 7444
info@u-blox.com

India
+91 959 1302 450
info_in@u-blox.com

Americas
+1 703 483 3180
info_us@u-blox.com

Japan
+81 3 5775 3850
info_jp@u-blox.com

APAC – Singapore
+65 6734 3811
info_ap@u-blox.com

Korea
+82 2 542 0861
info_kr@u-blox.com

China
+86 10 68 133 545
info_cn@u-blox.com

Taiwan
+886 2 2657 1090
info_tw@u-blox.com