

# NEO-M8 series

## u-blox M8 concurrent GNSS modules

### Highlights

- Concurrent reception of GPS/QZSS, GLONASS, BeiDou
- Industry leading -167 dBm navigation sensitivity
- Product variants to meet performance and cost requirements
- Combines low power consumption and high sensitivity
- Simple integration with u-blox cellular modules
- Backward compatible with NEO-7, NEO-6 and NEO-5 families



NEO-M8 series:  
12.2 x 16.0 x 2.4 mm

### Product description

The NEO-M8 series of standalone concurrent GNSS modules is built on the exceptional performance of the u-blox M8 GNSS (GPS, GLONASS, Galileo, BeiDou, QZSS and SBAS) engine in the industry proven NEO form factor.

The NEO-M8 series provides high sensitivity and minimal acquisition times while maintaining low system power. The NEO-M8M is optimized for cost sensitive applications, while NEO-M8N and NEO-M8Q provide best performance and easier RF integration. The NEO form factor allows easy migration from previous NEO generations. Sophisticated RF-architecture and interference suppression ensure maximum performance even in GNSS-hostile environments.

The NEO-M8 combines a high level of robustness and integration capability with flexible connectivity options. The future-proof NEO-M8N includes an internal Flash that allows

simple firmware upgrades for supporting additional GNSS systems. This makes NEO-M8 perfectly suited to industrial and automotive applications.

The DDC (I<sup>2</sup>C compliant) interface provides connectivity and enables synergies with most u-blox cellular modules. For RF optimization the NEO-M8N/Q features an additional front-end LNA for easier antenna integration and a front-end SAW filter for increased jamming immunity.

u-blox M8 modules use GNSS chips qualified according to AEC-Q100, are manufactured in ISO/TS 16949 certified sites, and fully tested on a system level. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

### Product selector

Model	Type							Supply	Interfaces				Features											
	GPS / QZSS	GLONASS	Galileo	BeiDou	Timing	Dead Reckoning	Precise Point Positioning	2.7 V – 3.6 V 1.65 V – 3.6 V	Lowest power (DC/DC)	UART	USB	SPI	DDC (I <sup>2</sup> C compliant)	Programmable (Flash)	Data logging	Additional LNA	Additional SAW filter	RTC crystal	Internal oscillator	Antenna supply	Antenna short circuit detection / protection	Antenna open circuit detection pin	Timepulse output	External interrupt / Wakeup
NEO-M8N	•	•	R	•				•	•	•	•	Sel	•	•	••	••	•	T	○	○	○	•	•	
NEO-M8Q	•	•		•				•	•	•	•	Sel	•		••	••	•	T	○	○	○	•	•	
NEO-M8M	•	•		•				•	•	•	•	Sel	•		+	+	•	C	○	○	○	•	•	

R = Galileo ready with future firmware  
 + = Suitable for most application (no additional component needed)  
 ++ = Additional onboard component for better performance

Sel = Select for either SPI or UART/DDC by HW configuration pin (D\_SEL)  
 ○ = Optional or requires external components  
 C = Crystal / T = TCXO

## Features

Receiver type	72-channel u-blox M8 engine GPS/QZSS L1 C/A, GLONASS L10F, BeiDou B1 SBAS L1 C/A: WAAS, EGNOS, MSAS Galileo-ready E1B/C (NEO-M8N)	
Nav. update rate <sup>1</sup>	Single GNSS:	up to 18 Hz
	Concurrent GNSS:	up to 10 Hz
Position accuracy <sup>2</sup>	2.0 m CEP	
Acquisition <sup>2</sup>	Cold starts:	26 s
	Aided starts:	2 s
	Reacquisition:	1.5 s
Sensitivity <sup>2</sup>	Tracking & Nav:	-167 dBm
	Cold starts:	-148 dBm
	Hot starts:	-156 dBm
Assistance	AssistNow GNSS Online AssistNow GNSS Offline (up to 35 days) <sup>3</sup> AssistNow Autonomous (up to 6 days) OMA SUPL & 3GPP compliant	
Oscillator	TCXO (NEO-M8N/Q), Crystal (NEO-M8M)	
RTC crystal	Built-In	
Noise figure	On-chip LNA (NEO-M8M). Extra LNA for lowest noise figure (NEO-M8N/Q)	
Anti jamming	Active CW detection and removal. Extra onboard SAW band pass filter (NEO-M8N/Q)	
Memory	ROM (NEO-M8M/Q) or Flash (NEO-M8N)	
Supported antennas	Active and passive	
Odometer	Travelled distance	
Data-logger	For position, velocity, and time (NEO-M8N)	

<sup>1</sup> For NEO-M8M/Q

<sup>2</sup> For default mode: GPS/SBAS/QZSS+GLONASS with TCXO

<sup>3</sup> NEO-M8M/Q: requires host integration

## Electrical data

Supply voltage	1.65 V to 3.6 V (NEO-M8M) 2.7 V to 3.6 V (NEO-M8N/Q)
Power consumption <sup>4</sup>	23 mA @ 3.0 V (continuous) 5 mA @ 3.0 V Power Save Mode (1 Hz, GPS mode only)
Backup Supply	1.4 to 3.6 V

<sup>4</sup> NEO-M8M

## Interfaces

Serial interfaces	1 UART 1 USB V2.0 full speed 12 Mbit/s 1 SPI (optional) 1 DDC (I <sup>2</sup> C compliant)
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Timepulse	Configurable 0.25 Hz to 10 MHz
Protocols	NMEA, UBX binary, RTCM

### Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.


The information contained herein is provided "as is" and u-blox assumes no liability for the use of the information. No warranty, either express or implied, is given, including but not limited, with respect to the accuracy, correctness, reliability and fitness for a particular purpose of the information. This document may be revised by u-blox at any time. For most recent documents, visit [www.u-blox.com](http://www.u-blox.com).

Copyright © 2014., u-blox AG

## Package

24 pin LCC (Leadless Chip Carrier): 12.2 x 16.0 x 2.4 mm, 1.6 g

Pinout



## Environmental data, quality & reliability

Operating temp.	-40° C to 85° C
Storage temp.	-40° C to 85° C (NEO-M8N/Q) -40° C to 105° C (NEO-M8M)

RoHS compliant (lead-free)

Qualification according to ISO 16750

Manufactured and fully tested in ISO/TS 16949 certified production sites

Uses u-blox M8 chips qualified according to AEC-Q100

## Support products

u-blox M8 Evaluation Kits:

Easy-to-use kits to get familiar with u-blox M8 positioning technology, evaluate functionality, and visualize GNSS performance.

EVK-M8N: u-blox M8 GNSS Evaluation Kit,  
with TCXO, supports NEO-M8N/Q

EVK-M8C: u-blox M8 GNSS Evaluation Kit,  
with crystal, supports NEO-M8M

## Ordering information

NEO-M8M-0	u-blox M8 Concurrent GNSS LCC Module, crystal, ROM, 12.2x16 mm, 250 pcs/reel
NEO-M8N-0	u-blox M8 Concurrent GNSS LCC Module, TCXO, flash, SAW, LNA, 12.2x16 mm, 250 pcs/reel
NEO-M8Q-0	u-blox M8 Concurrent GNSS LCC Module, TCXO, ROM, SAW, LNA, 12.2x16 mm, 250 pcs/reel

Available as samples and tape on reel

## Contact us

For contact information, see [www.u-blox.com/contact-us](http://www.u-blox.com/contact-us).