



N = Number of poles
 Dim A=(N-1)X7.62+5.62
 Dim B=(N-1)x7.62
 Dim C=(N-1)x7.62+12.2
 Dim D=(N-1)x7.62+18.0

Poles	Tolerance	
	DIM A&B	DIM C&D
2p-6p	±0.15	±0.25
7p-12p	±0.20	±0.30
13p-16p	±0.30	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	2006.01.20	The design of screw hole is changed	Marvin
△	2010.03.11	Add the 2P mark	Jacke
△	2011.08.09	The dimensions 2.6&3.2&6.0&8.3&0.9&5.8 are added	Aaron
△	2011.08.09	The Dim C&D are added	Aaron
△	2014.02.25	update the drawing	Chen Bo

Material

- Item ① Clamp: Brass(CuZn) Ni plated
- Item ② Terminal screw: Steel Zinc plating "-" slot type
- Item ③ Female contact: PhBz ,Tin plated
- Item ④ Terminal Cover: Thermoplastic (UL94V-0)
- Item ⑤ Terminal housing: Thermoplastic (UL94V-0)
- Item ⑥ With flange screw: Steel Zinc plating M2.5"/+/-" slot type

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 20A
- Wire range:
- Solid wire(AWG): 12-24
- Stranded wire(AWG): 12-24
- Torque: 5Lb-In
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval:

● Critical dimension: ▽

TJ xx 01 x 2 xxxx G

02 2 CONTACTS	0 Black (RAL9005)	G RoHS compliant (lead<4%) In copper Alloy 0000 Standard @ Logo 000A Standard ANY Logo Any special item by customer request, please contact sales department.
03 3 CONTACTS	2 Red (RAL3001/D)	
... ..	3 Orange(RAL2011/P)	
16 16 CONTACTS	4 Yellow(RAL1018/A)	
	5 Green(RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey(RAL7035/D)	
	9 White(RAL1102)	
	C Green(RAL6018/U)	

<h1>ANYTEK</h1>				<h2>CUSTOMER COPY</h2>			
				ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE TJ-7.62mm Series 2P-16P (With flange)							
PART NO. TJxx01x2xxxxG			DWG NO. 8TJ04.02				
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		
		Chen Bo	Chen Bo	Chen Bo			
		02/25 14	02/25 14	02/25 14			
						Tolerance	
				UNIT: mm		X. ±0.50	
				SCALE: NONE		X.X ±0.30	
				SHEET: 01/01		X.XX ±0.10	
				REV.: E		X° ±1°	