



Model: LP383454		Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	700	Overcharge Detection Voltage (V)	4.28±0.05
Battery pack specification (电池组规格)		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	750	Overdischarge Detection Voltage (V)	2.3±0.1
		Nominal Voltage 标称电压 (V)	3.7	Limited to Max loading current 仅用于最大的负载电流	
		Internal impedance 内阻 (≦) (mΩ, AC 1KHz)	200	峰值 2.0 (A)	持续 1.0 (A)
Ambient Conditions (环境温度)		Charge Temp. 充电温度 (°C)	0~45	Customer required Max loading current 客户要求最大的负载电流	
		Discharge Temp. 放电温度 (°C)	-20~60°	峰值 (A)	持续 (A)
		Humidity (湿度)	65±20%	客户要求的最大负载电流	
Battery protection (相关的电池保护值) Remark(备注): 1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象). 2. Robs compliant(严格按照ROHS要求生产). 3. Pulse discharge current:1A, max charge current:1.5A(客户设备放电脉冲电流1A, 最大充电电流: 5A).					

Title		LP383454-PCM-LD/	
File NO.		A09628	
EEMB BATTERY		EEMB BATTERY	
Drawn:	Wangyi	Revise No.:	E4-2009
Checked 1:	Huang Qinhuai	Projection:	
Checked 2:		Page:	1/1
Approved:		Scale:	1:1
Draw Date:	2014/05/08	Unit:	mm