

A	Dept	Qty
	DC	1
	ED	1
	IE	1
B	ISO	1
	PD	1
	R&D	1
	SD	1
	QA	1
	QC	1
	QE	1

Notes:

Specifications:

1. Contact Resistance: 20mΩ Max.
2. Insulation Resistance: 1000MΩ Min.
3. Dielectric Withstanding Voltage: 500V AC(rms)
For 1 Minute.
4. Current Rating:1.5A.
5. Temperature: -40°C~+105°C.

Materials:

1. Contact Material: Copper Alloy.
2. Contact Plating: Gold Plating Over Nickel.
3. Insulator Material: High temp,Black,UL94-V0.

Product Number Code:

Specifications:

- Materials:

- Product Number Code:

- Contacts type
R:R/A type
- Housing color
B:Black
- Contact plating
8: Full gold flash
- Connector type
S:Socket
- No.of contacts
2x2~2x40



GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1026-12-XXXXX-C		

 晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD