

# K802 GNSS Module

K Series GNSS Module

Ver.2022.10.25

17 mm



22 mm

**Size**(L × W × H): 22mm × 17mm × 2.8mm

**Weight:** 5g

## Features

BDS-3, BDS-2, GPS, GLONASS, Galileo, SBAS and QZSS

22mm×17mm

Certificated by AEC-Q104 Grade2

GNSS+INS navigation

0.6W power consumption

100Hz data output\*

## Applications



Autonomous  
Driving



UAV



Robotics



Precision  
Agriculture

# K802 GNSS Module

## Easy for integration

K802 is a 22mm×17mm×2.8mm module with surface-mounted design and is ideal for users to integrate. The power consumption is lower to 0.6W.

## Reliable performance with optimized algorithm

K802 module is embedded with ComNav's latest QUANTUM III SoC chip to provide reliable centimeter positioning accuracy in the most challenging dynamic conditions. The multi-frequency and its ability to track all the current and planned GNSS constellations enables it to receive much more satellite signals.

## Professional model certified by AEC-Q104 Grade2

K802 module certified by AEC-Q104 Grade2. It adheres to industrial standard quality specifications and production flow and strict qualification tests are performed to meet the standard of automotive industry.

## INS+GNSS navigation for continuous positioning

K802 is designed with an onboard high-precision IMU module for RTK positioning, which can provide continuous and high-quality positioning data with inertial navigation fusion algorithm where GNSS signal is lost.

**SinoGNSS**<sup>®</sup>  
By ComNav Technology Ltd.

2022, ComNav Technology Ltd. All rights reserved. **SinoGNSS** is the official trade mark of ComNav Technology Ltd., registered in People's Republic of China, EU, USA and Canada. All other trademarks are the property of their respective owners. (August, 2022).

# K802 GNSS Module

K Series GNSS Module

Ver.2022.10.25

## Signal Tracking

GPS	L1C/A, L2P,L2C
BDS	B1I,B2I,B1C,B2b
GLONASS	G1, G2
Galileo	E1,E5b
QZSS	L1C/A,L2C
SBAS	L1C/A

## Performance Specifications

Cold Start	< 20S(Adding Acceleration Capture Module)
Hot Start (with RTC)	< 10S(Typical)
Reacquisition	< 1s
RTK Initialization time	< 5S(baseline < 10km)
Initialization Reliability	> 99.9 %
Velocity accuracy	≤ 0.02 m/s (PDOP ≤4)
Time Accuracy	20ns
Overload	15g

## Positioning Specifications

Single Baseline RTK	8 mm + 1 ppm Horizontal 15 mm + 1 ppm Vertical
Post Processing	2.5 mm + 1 ppm Horizontal 5 mm + 1 ppm Vertical
DGPS	<0.4 m RMS
SBAS	1 m 3D RMS
Standalone	1.5m 3D RMS

## Communications

3 UART ports
1 SPI
1 Event Marker input
1 Pulse Per Second (PPS) output
3 I2C

## Anti-interference

Signal-to-interference rate is up to 50dB.

## Data Format

	-ASCII: NMEA-0183 GGA, GSA, GSV, RMC, HDT, ZDA, VTG, GST, GLL; PTNL, PJK; PTNL, AVR; PTNL, GGK
Position data output	'-ComNav Binary '-BINEX Data: 0x00, 0x01-01, 0x01-02, 0x01-05, 0x7d-00, 0x7e-00, 0x7f-05 '-Position data output rate: 1 Hz, 2 Hz, 5 Hz, 10 Hz,20Hz, 50Hz, 100Hz(optional)
Corrections data	RTCM 2.X, 3.X, CMR (GPS only), CMR+(GPS only)

## Antenna Interface

Impedance Match	50 Ohm
LNA Power External	+3.3V ~ +5.0V ± 5%VDC
LNA Gain	20 ~ 40dB

## Physical

Size (L × W × H)	22 mm×17 mm×2.8 mm
Weight	5 g
Hardware interface	LGA 54pin

## Environmental

Operating Temperature	-40℃ ~ +85℃
Storage Temperature	-55℃ ~+95℃

## Electrical

Voltage	+ 3.3V ~5.0V± 5 % DC
Power Consumption	0.6 W (Anti-interference off) Set anti-interference on consumes more about 0.2W

\*\*\*upgradeable

1. R(meter) is the length of two GNSS antennas.