



N=NUMBER OF POLES

Dim L	Nx5.08
Dim P	(N-1)x5.08

		TOL			
2P-6P	7P-12P	13P-18P	19P-24P		
Dim L	±0.15	±0.25	±0.35	±0.40	
Dim P	±0.15	±0.25	±0.35	±0.40	

SIGN	DATE	DESCRIPTION	APPROVER
△	10/16/14	Change the position of protruding point & update the drawing	Evan

THIS IS CAD DRAWING, DO NOT REVERSE MANUALLY!!!

- Material**
- Item ⊕ Terminal up housing: Thermoplastic (UL94V-0)
 - Item ⊖ Terminal down housing: Thermoplastic (UL94V-0)
 - Item ⊙ Terminal screw: Steel,Zinc plating "-" slot type
 - Item ⊕ Clamp: Brass, Ni plated
 - Item ⊖ Wire guard: Phbz ,Tin plated

- Electrical**
- Voltage rating: 300V
 - Current rating: 12A
 - Solid wire (AWG) : 12-24
 - Stranded wire (AWG) : 12-24
 - Torque (lb-in) : 4.3
 - Screw: M3
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Critical dimension: △

△ No. OF POLES

- 02 2 poles
 - 03 3 poles
 -
 - 24 24 poles
- K5 XX 51 X 0 XXXX G**
- Color
 - 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange(RAL2011/P)
 - 4 Yellow(RAL1018/A)
 - 5 Green(RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey(RAL7035/D)
 - C Green(RAL 6018/U)
- 0000: "@ Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request.
please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		K5 - 5.08 Series 2P-24P "-" screw (Without flange)	
PART NO.	K5xx51x0xxxxG	DWG NO.	8K50001
CHECKED	DESIGNED	DRAWN	
Evan	2014.10.16	Evan	2014.10.16
APPROVED		CUST NO.	
		UNIT:	mm
		SCALE:	NONE
		REV.:	C
		SHEET:	01/01
		Tolerance	X ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°