



N = Number of poles \triangle
 Dim L=(N-1)×3.81+14.2
 Dim B=(N-1)×3.81
 Dim C=(N-1)×3.81+9.0
 Dim D=(N-1)×3.81

Poles	Dim L	Dim B	Dim C	Dim D
2×2-2×6p	±0.15	±0.15	±0.15	±0.15
2×7-2×12p	±0.25	±0.25	±0.25	±0.25
2×13-2×18p	±0.35	±0.35	±0.35	±0.35
2×19-2×24p	±0.40	±0.40	±0.40	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
\triangle	1/29'07	Soldering temperature changed from 245° to 250°	Tony
\triangle	4/17'09	The design is changed	Jacke
\triangle	4/17'09	Add the tolerance table	Jacke
\triangle	4/17'09	The operating temperature is changed	Jacke
\triangle	2010.01.22	The demension is changed from 1.60mm to 1.10mm	Jacke
\triangle	2010.01.22	The demension is changed from 0.40mm to 0.20~0.30mm	Jacke
\triangle	2010.03.31	The material is changed from Brass to Copper	Jacke
\triangle	04/23'12	Flange nut is changed	Chen Bo
\triangle	04/23'12	The demension is changed from 1.50mm to 1.00mm	Chen Bo
\triangle	04/23'12	The Dimension Dim C & Dim D & 0.20 are added	Chen Bo
\triangle	04/23'12	The demension is changed from 7.1mm to 7.3mm	Chen Bo
\triangle	07/16'12	P.C.B. is changed and Dimension 22.0 is added	Chen Bo

- Material:
- Item \textcircled{a} Short contact pin: Copper Tin plated
 - Item \textcircled{b} Long contact pin: Copper Tin plated
 - Item \textcircled{c} Terminal(housing): Thermoplastic (UL94V-0)
 - Item \textcircled{d} With flange nut: Brass ,M2.5
 - Item \textcircled{e} Terminal(cover): Thermoplastic (UL94V-0)
- Electrical:
- Voltage rating: 300V
 - Current rating: 10A
 - Withstanding Voltage: 1.6 KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval:
 - Critical dimension: \triangle

VL xx 3 2 x 1 xxxx G

- No. OF POLES: 04: 2×2 POLES; 48: 2×24 POLES
- COLOR: 0 Black (RAL9005); 2 Red (RAL3001/D); 3 Orange(RAL2011/P); 4 Yellow(RAL1018/A); 5 Green(RAL6018/T); 6 Blue (RAL5015/A); 8 Grey(RAL7035/D)
- G: RoHS compliant (lead<4%) In copper Alloy
- 0000: "@ " Logo
- 000A: "ANYTEK" Mark
- Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		VL-3.81mm Right-angle Series with flange		
PART NO.	VLxx32x1xxxxG	DWG NO.	8VL0104	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
		Chen Bo 07/16'12	Chen Bo 04/23'12	
				Tolerance
		UNIT: mm		X. ±0.50
		SCALE: NONE		X.X ±0.30
		SHEET: 01/01		X.XX ±0.10
		REV.: G		X° ±1°