

P.C.B Layout

POLE	1	2	3	4	5	6	7	8	9	10	11	12
Dim.L	3.96	7.92	11.88	15.84	19.80	23.76	27.72	31.68	35.64	39.60	43.56	47.52
Dim.P	3.96	7.92	11.88	15.84	19.80	23.76	27.72	31.68	35.64	39.60	43.56	47.52
Tol.	±0.15						±0.25					
POLE	13	14	15	16	17	18	19	20	21	22	23	24
Dim.L	51.48	55.44	59.40	63.36	67.32	71.28	75.24	79.20	83.16	87.12	91.08	95.04
Dim.P	47.52	51.48	55.44	59.40	63.36	67.32	71.28	75.24	79.20	83.16	87.12	91.08
Tol.	±0.30						±0.40					

SIGN	DATE	DESCRIPTION	APPROVER
△	12/19/15	Update the drawing	Airy min
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material:

- Item ① Insulating body: Thermoplastic (UL94V-0)
- Item ② contact pin: Brass Bright Tin plated over Nickel plated.
- Item ③ Insulating lever: Thermoplastic (UL94V-0)
- Item ④ Spring clamp: Stainless steel
- Item ⑤ Side Cover: Thermoplastic (UL94V-0)

Electrical:

- Voltage rating: 300V
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 16-20
- Stranded wire(AWG): 16-20
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C ±5°C/5 Sec

- △ Safety Approval: cULus
- △ Critical dimension: △



HB xx 41 x 0 xxxx G

No. OF POLES
 △01: 1 POLES
 :
 24: 24 POLES
 COLOR
 2: RED
 3: ORANGE
 5: GREEN
 8: GREY



RoHS compliant △
 (lead<4%)
 In copper Alloy

0000 Standard @ Logo
 000A Standard ANY Logo
 Any special item by
 customer request,
 please contact sales
 department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR, PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		HB 3.96 mm With lever Series				DWG NO.				8HB0601	
PART NO.		HBxx41x0xxxxG				DWG NO.		8HB0601			
APPROVED		CHECKED	DESIGNED	DRAWN		CUST NO.		Tolerance			
			Airy min	Airy min			UNIT: mm		X. ±0.50		
			2015.12.19	2015.12.19			SCALE: NONE		X.X ±0.30		
							SHEET: 01/01		REV: C		
									X° ±1°		