



SIGN	DATE	DESCRIPTION	APPROVER
Δ	06/28'13	Add the dimensional label	Jacky
Δ	06/28'13	Add the terminal lever colour	Jacky
Δ	06/28'13	Add the colour code	Jacky
Δ	06/28'13	Change the drawing number	Jacky
Δ	06/28'13	Add the view	Jacky

Material: THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Item ① Terminal(lever): Thermoplastic (UL94V-0)Orange Δ
- Item ② Terminal(up body): Thermoplastic (UL94V-0)
- Item ③ Wire guard: Stainless steel
- Item ④ Male contact pin: Phbz. Tin plated
- Item ⑤ Flange screw NUT: Brass M 2.5
- Item ⑥ Terminal(down body): Thermoplastic (UL94V-0)

- Electrical: cULus
- Voltage rating: 300 V
 - Current rating: 4 A
 - Wire range:
 - Solid wire(AWG): 16-28
 - Stranded wire(AWG): 16-28
 - Wire strip length: 9-10 mm
 - Withstanding Voltage: 1.6 KV
 - Operating temperature: -40°C to +115°C
 - Safety Approval:
 - Critical dimension: Δ

H5 xx 1 0 x 2 xxxx G

No. OF POLES
02: 2 POLES
:
24: 24 POLES

COLOR
0: BLACK
5: GREEN (RAL 6018/T)
6: BLUE
8: GREY (RAL 7035/D)
Δ C: GREEN(RAL 6018/U)

RoHS compliant (lead<4%)
In copper Alloy
0000: "@ " Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request. please contact sales department.

DIM	TOL				
	2P-6P	7P-12P	13P-18P	19P-24P	
DimA	(N-1)×3.5+4.3	±0.10	±0.15	±0.20	±0.30
DimB	(N-1)×3.5	±0.10	±0.15	±0.20	±0.30
DimC	(N-1)×3.5+8.6	±0.15	±0.20	±0.30	±0.40
DimD	(N-1)×3.5+13.8	±0.15	±0.20	±0.30	±0.40

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		H5 3.5mm Flange with NUT Series					
PART NO.		H5xx10x2xxxxG		DWG NO.		8H50103 Δ	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Jacky 2013.06.28	Jacky 2013.06.28			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
		SHEET: 01/01		REV.: C			