



Dimension

DIM A	N×5.0+0.10
DIM B	(N-1)×5.0
Δ DIM C	(N+1)×5.0
Δ DIM D	N×5.0+10.6
Δ DIM E	N×5.0+0.4

N=Number of poles

POLES	TOL
2p-6p	±0.15
7p-12p	±0.20
13p-16p	±0.30
17p-24p	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
Δ	06/22'13	Add the dimensional label	Jacky
Δ	06/22'13	Add the feminal lever colour	Jacky
Δ	06/22'13	Add the colour code	Jacky
Δ	06/22'13	Change the drawing number	Jacky
Δ	06/22'13	Add the view	Jacky
Δ	06/28'13	Change the dimension from 5.2 to 5.0	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item a Terminal body:Thermoplastic (UL94V-0)
- Item b Terminal body:Thermoplastic (UL94V-0)
- Item c Terminal lever:Thermoplastic (UL94V-0)Orange
- Item d Wire guard:Stainless Steel
- Item e Male contacta pin:PhBz (CuSn) Tin plated
- Item f With flange Nut; Brass M2.5

Electrical

- Voltage rating: 300V
- Current rating: 10A
- Solid wire(AWG): 12-26
- Stranded wire(AWG): 12-26
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval:
- Critical dimension:

H5 xx 70 x 2 xxxx G

- 02 2 CONTACTS
 - 03 3 CONTACTS
 -
 - 24 24 CONTACTS
- 0: BLACK
5: GREEN (RAL 6018/T)
6: BLUE
8: GREY (RAL 7035/D)
ΔC: GREEN (RAL 6018/U)
- 0000 Standard @ Logo
000A Standard ANY Logo
Any special item by customer request, please contact sales department.
- RoHS compliant (lead<4%)
In copper Alloy

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		H5 5.0 Series (2P-24P) Flange with Nut			
PART NO.	H5xx70x2xxxxG	DWG NO.	8H50303Δ		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Jacky 2013.06.28	Jacky 2013.06.28		X. ±0.50 X.X ±0.30 X.XX ±0.10 X* ±1*
SHEET: 01/01				REV.: C	