



RAYSTAR

RAYSTAR Optronics, Inc.
曜凌光電股份有限公司



曜凌光電股份有限公司
Raystar Optronics, Inc.

T: +886-4-2565-0761 | F: +886-4-2565-0760
sales@raystar-optronics.com | www.raystar-optronics.com

RFA180G-ALW-DNN

SPECIFICATION

General Specifications

- Size: 1.77 inch
- Dot Matrix: 128 x RGB x 160(TFT) dots
- Module dimension: 34.0(W) x 45.83(H) x 2.65(D) mm
- Active area: 28.03 x 35.04 mm
- Dot pitch: 0.073 x 0.219 mm
- LCD type: TFT, Normally White, Transmissive
- View Direction: 6 o'clock
- Gray Scale Inversion Direction: 12 o'clock
- Aspect Ratio: Portrait
- IC: ST7735S or Equivalent
- Interface: SPI
- Backlight Type: LED, Normally White
- Touch Panel: Without Touch Panel
- Surface: Anti-Glare


*Color tone slight changed by temperature and driving voltage.

Interface

LCM PIN Definition

Pin	Symbol	I/O	Function
1	LED+	P	Back light anode
2	LED-	P	Back light cathode
3	SPI4W (VCC=4 WIRE)	I	- SPI4W='0', 3-line SPI Enable. - SPI4W='1', 4-line SPI Enable. -If Not Used, Please fix this Pin at DGND Level.
4	VCC	P	Power Supply.
5	GND	P	Ground
6	CS	I	Chip enable (CSX)
7	RST	I	Reset signal (RESX)
8	SDA	I/O	Serial input/output signal in serial interface mode.
9	SCL	I	In Serial Interface, this is used as SCL.
10	D/C	I	Data/ command selection. (D/CX)

Contour Drawing



Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Operating conditions

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For Analog	VCC	—	2.5	2.75	3.7	V
Supply LCM current	ICC	—	-	0.9	2	mA

LED driving conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current		-	40	-	mA
Power Consumption			128	-	mW
LED voltage	VBL+	2.9	3.2	3.4	V
LED Life Time		-	50,000	-	Hr