



P.C.B. LAYOUT

N = Number of poles
 Dim A=(N-1)x3.81+2.8
 Dim B=(N-1)x3.81
 Dim C=(N-1)x3.81+14.2
 Dim D=(N-1)x3.81+9.0
 Dim E=(N-1)x3.81

	Dim A	Dim B	Dim C	Dim D	Dim E
2-5p	±0.10	±0.10	±0.10	±0.10	±0.10
6-10p	±0.15	±0.15	±0.15	±0.15	±0.15
11-15p	±0.20	±0.20	±0.20	±0.20	±0.20
16-20p	±0.25	±0.25	±0.25	±0.25	±0.25
21-24p	±0.30	±0.30	±0.30	±0.30	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	7/23'08	With flange type is changed	Marvin
△	7/23'08	Operating temperature is changed	Marvin
△	11/14`09	The design is changed from the round hole to hexagonal hole.	Jacke
△	01/12`10	Add cULus standard	Jacke
△	08/10`13	change the dimension from 0.93 to 1.07	Chen Bo
△	08/10`13	update the drawing	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Materials

- Item a Terminal body:Thermoplastic (UL94V-0)
- Item b Female contact:PhBz(CuSn), Tin plated
- Item c With Flange Nut :Brass M2.5

Electrical

- Voltage rating: 300V AC
- Current rating: 8A
- Withstanding Voltage: 1.6kv
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval: us

V7 xx 3 2 x 0 xxxx G

- No. OF POLES
- 02 2 CONTACTS
 - 03 3 CONTACTS
 -
 - 24 24 CONTACTS

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- 9 White(RAL1102)
- C Green(RAL6018/U)

G RoHS compliant (lead<4%) In copper Alloy

0000: "@" Logo (Standard)
 000A: "ANYTEK" Mark
 Any special item by customer request.
 please contact sales department.

ANYTEK				CUSTOMER COPY				
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD								
TITLE		V7 3.81 series Vertical With flange				DWG NO.		8V70104
PART NO.		V7xx32x0xxxxG				CUST NO.		
APPROVED		CHECKED		DESIGNED		DRAWN		Tolerance
				Chen Bo 08/10`13		Chen Bo 08/08`13		X. ±0.5 X.X ±0.3 X.XX ±0.1 X° ±1°
						SHEET: 01/01		UNIT: mm SCALE: NONE REV.: F